



Swiftpro™ K30 Single Sided Retransfer Card Printer

Swiftpro provides market-leading solutions with an extensive range of retransfer desktop solutions to meet the needs of the customer and by adding value to global businesses. Our mission is to revolutionize business identity and access management by building trusted partnerships through our simple SMART™ partner distribution networks.

The Swiftpro K30 retransfer card printer has an outstanding print quality for single-sided printing and is upgradeable to double-sided printing. With 300dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management.

The ultra-fast, powerful Swiftpro K30 printer is available with contact and contactless smart card encoding technologies and 100-card input and output hoppers, with an optional 250-card input hopper upgrade. This reliable and durable printer is the ideal solution for both entry level to advanced secure card programs for a range of vertical markets.

Selecting the right printer is important. Equally if not more important is using Genuine Swiftpro Supplies. They are critical to delivering printer reliability, print quality and vibrant colors for your card programs. Swiftpro supplies deliver consistency and ensure the longevity of your printer and print head and minimize downtime and create efficiencies in your card programs. Always ask for Genuine Swiftpro Supplies from your Authorized Premiere Value Added Distributor, Premiere Enterprise Solution Provider or Premiere Value- Added Reseller.



SECURITY

The ribbon erase function prevents leakage of personal information on the monochrome black panel ink ribbon. It scrambles information beyond recognition to protect this data.



VERSATILITY

Swiftpro's modular design permits customers to upgrade as their card programs need changes.



IMAGE QUALITY

High Resolution printing using 300 dpi printing provides superior print quality for all your card programs.



RELIABILITY

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.



INNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organizations since 1989.



DURABILITY

Highly durable printers with industry leading warranties on all our products and lifetime on the print head.



Swiftpro K30 Single Sided



CORPORATE



EDUCATION



FINANCE



HEALTHCARE



RETAIL



TRANSPORT



GOVERNMENT

Printing

- Dye Sublimation Retransfer
- Full Color Retransfer
- printing Single Sided Printing
- Up to 130 Cards Per Hour
- 256 Gradation Printing
- Over the Edge Printing on CR80, ID-1 Cards

Standard Features

- USB & Ethernet connectivity
- 100-Card Input Hopper
- (30mil) 100-Card Output
- Hopper (30mil) LCD Panel
- 300 DPI Print Resolution
- 36 Month Printer Warranty
- Lifetime Printhead
- Warranty Microsoft Certified Drivers
- Solenoid Electronic Lock for Card Input
- Hopper
- Solenoid Electronic Lock for Supplies / Front
- Door Housing Software-controlled Lock/
- Unlock from Status Monitor K Ribbon Erase
- Function
- IPSec Security for Secure Data Encryption IPv6
- and IPv4 Inline Bend Remedy
- MAC Address Forced Printing (UV Panel on
- Card) Kensington Lock

Encoding*

- Contactless Encoder, Omnikey 5127 (iClass, MIFARE and DESFire)
- Contact Encoder (CF-7CRW / Control
- board) Contact Encoder (CF-7CCS/
- IC Contact Station)

Software Supported

- CardPresso
- Card Exchange
- All Card Personalizations software used through Swiftpro Driver*
- *check with Software vendor, as some features may be limited for use on Swiftpro Printers
- Microsoft® Windows® 7, 8, 10 32bit /
- 64bit Microsoft® Windows® Server 2008
- R2 (SP1) 64bit Microsoft®
- Windows® XP Server 2012 64bit

Swiftpro Genuine Color Ribbons

- YMCK-1000 Yield
- YMCKP Peel Off Ribbon - 750
- Yield YMCKUV-750 - Yield
- InTM Retransfer Film - 1000 Yield

Physical Specification

Height	13.19 in (335 mm)	Without Card
Width	13.5 in (343 mm)	Without Card
Depth	12.68 in (322 mm)	Without Card
Weight	29.76 lb ^P (13.5 kg)	

Interface

- USB 2.0 (Hi-speed / Full
- Speed) Ethernet (100BASE-TX / 10BASE-T)

Options

- Flipper Unit
- Magstripe and Contact and Contactless Encoders per description to left

Electrical

- Temperature: 59°F to 86°F (15°C to 30°C)
- Humidity: 35% to 70% (YMCK Ink, No
- Condensation) 3.5A (110V system) 1.6A
- (220V system)
- 310W (maximum power when all
- options are installed)

Card Specification

- Card Thickness 10-40mil
- Card Size ISO 7810 Format, CR80,
- ID-1 Card Material: PVC, PC, PET, PET-G
- Technology Cards Contact and or
- Contactless with and Without Mag Stripe

* Magnetic stripe encoding is available with an upgrade to duplex printing.



Technical Support: support@unicard.com.au
Sales: sales@unicard.com.au | Ph: (02) 9437 1777
www.unicard.com.au

Swiftpro®